



**Example: 4LN6.0-220AU** (4 Legs, No Dimple, 6mm, 220 g Activation Force , Gold plated )

**Reference:**

**4L:** 4 Legs - **N:** No Dimple - **D:** with Dimple - **Ø** mm - **Force** (g) – **Plating:** **SS** (Stainless Steel), **NI(S)** (Nickel contact side, Stainless Steel), **NI** (Nickel both sides), **AU** (Gold contact side , Stainless Steel)

Force	Ø 6 mm	Ø 7 mm	Ø 8.5 mm	Ø 10.0 mm Ø 10.5 mm	Ø 12.2 mm Ø 14.0 mm	Ø 16 mm Ø 20 mm
200	4LN6.0-200AU	4LN7.0-200SS 4LN7.0-200AU	4LN8.5-200NI 4LD8.5-200NI	4LD10.0-200AU		
220	4LD6.0-220AU			4LD10.0-220NI(S) 4LN10.0-220AU	4LN12.2-220NI 4LD12.2-220NI 4LN12.2-220AU 4LD12.2-220AU	
260			4LN8.5-260NI 4LD8.5-260NI 4LD8.5-260AU	4LN10.5-260NI 4LN10.5-260AU	4LN12.2-260NI 4LN12.2-260AU	
280			4LN8.5-280AU	4LN10.0-280NI(S) 4LD10.0-280NI(S) 4LN10.0-280AU 4LD10.0-280AU		
300			4LD8.5-300NI			
320	4LD6.0-320NI		4LD8.5-320AU	4LD10.0-320NI(S) 4LN10.0-320AU	4LN12.2-320SS 4LN12.2-320NI 4LD12.2-320SS 4LD12.2-320NI 4LN12.2-320AU 4LD12.2-320AU	4LN16.0-320NI 4LD16.0-320SS 4LD16.0-320NI
340				4LD10.0-340AU		4LN16.0-340AU
350				4LD10.0-350NI(S)	4LN14.0-350SS	
380					4LN12.2-380NI	
400				4LN10.0-400AU 4LD10.0-400AU	4LN12.2-400AU 4LD12.2-400AU	4LD16.0-400NI(S) 4LD20.0-400NI
420			4LD8.5-420NI 4LD8.5-420AU			4LN16.0-420NI
450				4LD10.0-450NI(S)	4LN12.2-450NI 4LN12.2-450AU	
500						4LD20.0-500NI